



AMG-NVR

64Ch NVR

AMG-EHR-4000-Series 64 Ch ,4K Network Video Recorder.

Series Features

AMG-EHR-4064-04/08 (4 and 8 SATA)



Key Highlights:

4K 64 Ch NVR with 4 and 8 SATA.

18 TB Storage Per Slot.

Recording Bandwidth: 550 Mbps.

Recording Resolution : 16MP/12MP/8MP/5MP/4MP/3MP/1080P/960P/720P/D1/2CIF/CIF

Approvals



AMG-EHR-4064-4	AMG-EHR-4064-8
Max Ch: 64	Max Ch: 64
HDD Slots: 4	HDD Slots: 8.
HDD: 18Tb/Slot	HDD: 18Tb/Slot
Remote Users: 10	Remote Users: 10
Video/Audio Output HDMI: 12MP @30,4K (3840x2160) @30, 1920x1080p@60, 1920x1080p@50, 1600x1200@60, 1280x1024@60, 1280x720@60, 1024x768@60	Video/Audio Output HDMI: 12MP @30,4K (3840x2160) @30, 1920x1080p@60, 1920x1080p@50, 1600x1200@60, 1280x1024@60, 1280x720@60, 1024x768@60
Recording Resolution: 16MP/12MP12MP/4K/5MP/4MP/3MP/1080P/960P/720P/D1/2CIF	Recording Resolution: 16MP/12MP12MP/4K/5MP/4MP/3MP/1080P/960P/720P/D1/2CIF
Audio Output: 1-ch, 3.5mm	Audio Output: 1-ch, 3.5mm
Audio Compression: G.711A, G.711U	Audio Compression: G.711A, G.711U
Synchronous Playback: 64ch	Synchronous Playback: 54ch
Live view display: 1/4/6/8//12/16/32/64	Live view display: 1/4/6/8//12/16/24/32/64
Network: 1 RJ45 10M/100M	Network: 1 RJ45 10M/100M
Recording Stream: Multiple	Recording Stream: Multiple
Action: Record, Email (Text), Email (Snapshot), FTP, Buzzer, e-PTZ Control (Go to Pre-Set), NVR DO, Camera D	Action: Record, Email (Text), Email (Snapshot), FTP, Buzzer, e-PTZ Control (Go to Pre-Set), NVR DO, Camera D
Incoming Bandwidth: 550 Mbps Outgoing Bandwidth: 550 Mbps	Incoming Bandwidth: 550 Mbps Outgoing Bandwidth: 550 Mbps
USB: 3x USB 2.0	USB: 2x USB 2.0; 2x USB 3.0
e-SATA: Yes	e-SATA: Yes
User Management: User Account: 7 (1 admin & 6 User)	User Management: User Account: 7 (1 admin & 6 User)
Protocol: HTTPS, HTTP, TCP/IP, IPV4, IPV6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP filter, PPPOE, DDNS, P2P, IP Search, ONVIF, NFS/SMB/CIFS	Protocol: HTTPS, HTTP, TCP/IP, IPV4, IPV6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP filter, PPPOE, DDNS, P2P, IP Search, ONVIF, NFS/SMB/CIFS
Event: Motion Detection, PIR Detection, Tempering Detection, Customer Flow Statistics, Face Attendance, Face Detection & Recognition, Heat Map, Human & Vehicle Detection, Penetration Detection, Line Cross Detection, Queue Length Detection, Recognized Population Statics, SOD, Deterrence, Digital Input (Camera), Digital Output (Camera), Connection abnormal, Storage Abnormal, Storage Full, Camera Network Loss.	Event: Motion Detection, PIR Detection, Tempering Detection, Customer Flow Statistics, Face Attendance, Face Detection & Recognition, Heat Map, Human & Vehicle Detection, Penetration Detection, Line Cross Detection, Queue Length Detection, Recognized Population Statics, SOD, Deterrence, Digital Input (Camera), Digital Output (Camera), Connection abnormal, Storage Abnormal, Storage Full, Camera Network Loss.
Operating Temperature: 0°C - 40°C	Operating Temperature: 0°C - 40°C
Safety Certifications: CE, FCC, UL & BIS	Safety Certifications: CE, FCC, UL & BIS
Rack mount: 2U	Rack mount: 2U

<https://amgsecurities.com/>