

## AMG-NVR

## 32/64Ch NVR

AMG-EHR-4000-Series 32/64 Ch ,4K Network Video Recorder.

### Series Features

AMG-EHR-4032-08 (8 SATA)  
AMG-EHR-4064-16 (16 SATA)



### Key Highlights:

4K 32/64 Ch NVR with 8/16 SATA.  
08 TB Storage Per Slot.  
Recording Bandwidth: 650 Mbps  
Two Way Audio Option  
System Support Raid Configuration: 0,1,5,6,10.

AMG-EHR-4032-8	AMG-EHR-4064-16
Max Ch: 32	Max Ch: 64
HDD Slots: 8	HDD Slots: 16.
HDD: 8Tb/Slot	HDD: 08Tb/Slot
Remote Users: 10	Remote Users: 12
Video/Audio Output HDMI: 12MP @30FPS,4K (3840x2160) @30 FPS, 1920x1080p@60 FPS, 1024x768 @ 60FPS 1600x1200@30 FPS, 1280x1024@60 FPS,1280x720@ FPS 60.	Video/Audio Output HDMI: 12MP @30FPS,4K (3840x2160) @30 FPS, 1920x1080p@60 FPS, 1024x768 @ 60FPS 1600x1200@30 FPS, 1280x1024@60 FPS,1280x720@ FPS 60.
Network Connectivity: Dual 10/100/1000 Base-T Network Port	Network Connectivity: Dual 10/100/1000 Base-T Network Port
Recording Resolution: 12MP/4K/5MP/4MP/3MP/1080P/960P/720P/D1/2CIF	Recording Resolution: 12MP/4K/5MP/4MP/3MP/1080P/960P/720P/D1/2CIF
Audio Output: 1-ch, 3.5mm	Audio Output: 1-ch, 3.5mm
Audio Compression: G.711A, G.711U	Audio Compression: G.711A, G.711U
Synchronous Playback: 32ch	Synchronous Playback: 64ch
Live view display: 1/4/6/9/12/16/32	Live view display: 1/4/6/9/12/16/24/32/64
Compression: H.265, H,264	Compression: H.265, H,264
Recording Stream: Multiple	Recording Stream: Multiple
Action: Record, Email (Text), Email (Snapshot), FTP, Buzzer, e-PTZ Control (Go to Pre-Set), NVR DO, Camera D	Action: Record, Email (Text), Email (Snapshot), FTP, Buzzer, e-PTZ Control (Go to Pre-Set), NVR DO, Camera D
NVR Bandwidth: 650 Mbps Outgoing	NVR Bandwidth: 650 Mbps Outgoing
Inputs: Front 2x USB 2.0, Rear 1x USB 3.0, Front 1x HDMI, Rear 1x HDMI, 1x VGA	Inputs: Front 2x USB 2.0, Rear 1x USB 3.0, Front 1x HDMI, Rear 1x HDMI, 1x VGA
e-SATA: Yes, UPTO 18TB	e-SATA: Yes, UPTO 18TB
User Management: User Account: 7 (1 admin & 6 User)	User Management: User Account: 10 (1 admin & 9 User)
Protocol: HTTPS, HTTP, TCP/IP, IPV4, IPV6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP filter and Multi IP configuration, PPPOE, DDNS, P2P, IP Search, ONVIF, NFS/SMB/CIFS	Protocol: HTTPS, HTTP, TCP/IP, IPV4, IPV6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP filter and Multi IP configuration, PPPOE, DDNS, P2P, IP Search, ONVIF, NFS/SMB/CIFS
Alaram/Event: Motion Detection, Panic Detection, Tempering Detection, Customer Flow Statistics, Face Attendance, Face Detection & Recognition, Heat Map, Human & Vehicle Detection, Penetration Detection, Line Cross Detection, Queue Length Detection, Recognized Population Statics, SOD, Deterrence, Digital Input (Camera), Digital Output (Camera), Connection abnormal, Storage Abnormal, Storage Full, Camera Network Loss.	Alaram/Event:: Motion Detection, Panic Detection, Tempering Detection, Customer Flow Statistics, Face Attendance, Face Detection & Recognition, Heat Map, Human & Vehicle Detection, Penetration Detection, Line Cross Detection, Queue Length Detection, Recognized Population Statics, SOD, Deterrence, Digital Input (Camera), Digital Output (Camera), Connection abnormal, Storage Abnormal, Storage Full, Camera Network Loss.
Video Extraction: AVI, MOV, and MP4.	Video Extraction: AVI, MOV, and MP4.
Power supply: 100-240V AC / 60-50 Hz ±10%, 300W.	Power supply: 100-240V AC / 60-50 Hz ±10%, 300W.
Operating temperature: -15°C to +50°C	Operating temperature: -15°C to +50°C
Humidity :75% (non-condensing)	Humidity :75% (non-condensing)
Safety Certifications: CE, RoHS, FCC, UL/EN & BIS	Safety Certifications: CE, RoHS, FCC, UL/EN & BIS
Rack mount: 2U	Rack mount: 3U

### Rear Panel

