

AMG-NVR

32/64Ch NVR

AMG-EHR-4000-Series 32/64 Ch ,4K Network Video Recorder.

Series Features

AMG-EHR-4032-08 (8 SATA)
AMG-EHR-4064-16 (16 SATA)



Key Highlights:

4K 32/64 Ch NVR with 8/16 SATA.
16 TB Storage Per Slot.
Bandwidth: 768 Mbps
Two Way Audio Option
System Support Raid Configuration: 0,1,5,6,10.

AMG-EHR-4032-8	AMG-EHR-4064-16
Max Ch: 32	Max Ch: 64
HDD Slots: 8	HDD Slots: 16.
HDD: 16Tb/Slot	HDD: 16Tb/Slot
Remote Users: 128	Remote Users: 128
Video/Audio Output HDMI: 12MP @30FPS,4K (3840x2160) @30 FPS, 1920x1080p@60 FPS, 1024x768 @ 60FPS 1600x1200@30 FPS, 1280x1024@60 FPS,1280x720@ FPS 60.	Video/Audio Output HDMI: 12MP @30FPS,4K (3840x2160) @30 FPS, 1920x1080p@60 FPS, 1024x768 @ 60FPS 1600x1200@30 FPS, 1280x1024@60 FPS,1280x720@ FPS 60.
Network Connectivity: Dual 10/100/1000 Base-T Network Port	Network Connectivity: Dual 10/100/1000 Base-T Network Port
Recording Resolution: 32MP/12MP/4K/5MP/4MP/3MP/1080P/960P/720P/D1/2CIF	Recording Resolution: 32MP/12MP/4K/5MP/4MP/3MP/1080P/960P/720P/D1/2CIF
Audio Output: 1-ch, 3.5mm	Audio Output: 1-ch, 3.5mm
Audio Compression: G.711A, G.711U	Audio Compression: G.711A, G.711U
Synchronous Playback: 32ch	Synchronous Playback: 64ch
Live view display: 1/4/6/9//12/16/32/48	Live view display: 1/4/6/9//12/16/24/32/64
Compression: H.265, H.264	Compression: H.265, H.264
Recording Stream: Multiple	Recording Stream: Multiple
Action: Record, Email (Text), Email (Snapshot), FTP, Buzzer, e-PTZ Control (Go to Pre-Set), NVR DO, Camera D	Action: Record, Email (Text), Email (Snapshot), FTP, Buzzer, e-PTZ Control (Go to Pre-Set), NVR DO, Camera D
NVR Bandwidth: 768 Mbps	NVR Bandwidth: 768 Mbps
Inputs: Front 2x USB 2.0, Rear 1x USB 3.0, 2 x HDMI, 1x VGA	Inputs: Front 2x USB 2.0, Rear 1x USB 3.0, 2 x HDMI, 1x VGA
e-SATA: Yes, UPTO 18TB	e-SATA: Yes, UPTO 18TB
User Management: User Account: 7 (1 admin & 6 User)	User Management: User Account: 10 (1 admin & 9 User)
Protocol: HTTPS, HTTP, TCP/IP, IPV4, IPV6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP filter and Multi IP configuration, PPPOE, DDNS, P2P, IP Search, ONVIF, NFS/SMB/CIFS	Protocol: HTTPS, HTTP, TCP/IP, IPV4, IPV6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP filter and Multi IP configuration, PPPOE, DDNS, P2P, IP Search, ONVIF, NFS/SMB/CIFS
Alarm/Event: Motion Detection, Panic Detection, Tempering Detection, Customer Flow Statistics, Face Attendance, Face Detection & Recognition, Heat Map, Human & Vehicle Detection, Penetration Detection, Line Cross Detection, Queue Length Detection, Recognized Population Statics, SOD, Deterrence, Digital Input (Camera), Digital Output (Camera), Connection abnormal, Storage Abnormal, Storage Full, Camera Network Loss, Motor Vehicle Search; Non- Motor Vehicle Search; Human Body Search; General Search; People Counting Report.	Alarm/Event: Motion Detection, Panic Detection, Tempering Detection, Customer Flow Statistics, Face Attendance, Face Detection & Recognition, Heat Map, Human & Vehicle Detection, Penetration Detection, Line Cross Detection, Queue Length Detection, Recognized Population Statics, SOD, Deterrence, Digital Input (Camera), Digital Output (Camera), Connection abnormal, Storage Abnormal, Storage Full, Camera Network Loss, Motor Vehicle Search; Non- Motor Vehicle Search; Human Body Search; General Search; People Counting Report; Heat Map, Smoke and Fire Detection
Vehicle Picture Library: Up to 5 vehicle picture libraries, with up to 5K to 10K vehicle pictures in total	Vehicle Picture Library: Up to 5 vehicle picture libraries, with up to 25K vehicle pictures in total
Capacity of Snapshot Records: 1 million records for face snapshot; 1 million records for vehicle snapshot for video Metadata.	Capacity of Snapshot Records: 3 million records for face snapshot; 2 million records for vehicle snapshot; 2 million records for SIP; 2 million records for video Metadata.
Video Extraction: AVI, MOV, and MP4.	Video Extraction: AVI, MOV, and MP4.
Power supply: 100-240V AC / 60-50 Hz ±10%, 300W.	Power supply: 100-240V AC / 60-50 Hz ±10%, 300W.
Operating temperature: -15°C to +50°C	Operating temperature: -15°C to +50°C
Humidity :75% (non-condensing)	Humidity :75% (non-condensing)
Safety Certifications: CE, RoHS, FCC, UL/EN & BIS	Safety Certifications: CE, RoHS, FCC, UL/EN & BIS
Rack mount: 2U	Rack mount: 3U

Rear Panel

